

ZINC RAY / WASHER SURFACE MOUNTED

Zinc is designed to contrast with the existing blocky linear floodlights and spotlights. Where developers are trying to hide fixtures using additional architectural details to reduce their visual impact, it is time to display a performance tool without being apologetic. Zinc offers a high performance outdoor fixture with pleasing aesthetics and unobtrusive form.

Zinc line leaves minimal physical impact while blending smoothly within its environment. In spite the compact design Zinc luminaires can host different optics to serve different lighting situations.

This product can be mounted vertically or horizontally and has a tilt adjustment up to 90°, allowing designers to illuminate horizontal, sloped, and vertical surfaces alike.

Product Features:

- Homogeneous color mixing within one reflector
- Uniformity of 1:4
- IP 65
- Different optics serving different lighting application:
 - o Wall washer
 - o Wall grazer
 - o Flood light



Luminaire

Application:	Washer
Body Material:	Extruded aluminium
Glass Cover:	Black Serigraphy

Installation

Ambient Temperature: -10 to 40°C

Optics



Optic Type: Metallized Faceted Reflectors

Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz

Control Gear Efficacy: > 85%


Polar Curve



We reserve the right to make technical changes without prior notice

ZINC / WASHER SURFACE MOUNTED

Mounting Ratio



Height/6 to Height/5

Setback from the wall is defined by wall texture and height. Consult factory for optimal setback according to your project conditions.

ZINC / WASHER SURFACE MOUNTED

Code Index:

<u>Z 3</u>	<u>R</u>	<u>O S M</u>	<u>W O</u>	<u>X X</u>	---	---	<u>6 5</u>	---	---	---
Family	Product	Mounting	Optic	Beam Angle	CRI/CCT & Power	Control	IP	Body Finish	Length	Wiring
					927M1	C		BS	30	BB
					927M2	D		WS	60	BI
					927M3	E		GS	90	HB
					930M1					HI
					930M2					M
					930M3					E
					940M1					
					940M2					
					940M3					

Family	Product	Mounting	Optic	Beam Angle
Z3 Zinc	R Ray	OSM Surface Mounted	WO Cut-off Washer	XX N/A

CRI/CCT & Power	Control	IP	Body Finish	Length
<p>LED Load initial Lumen</p> <p>2700°K</p> <p>927M1: 28 W/m 2250 lm/m</p> <p>927M2: 40 W/m 3050 lm/m</p> <p>927M3: 56 W/m 3950 lm/m</p> <hr/> <p>3000°K</p> <p>930M1: 28 W/m 2300 lm/m</p> <p>930M2: 40 W/m 3150 lm/m</p> <p>930M3: 56 W/m 4150 lm/m</p> <hr/> <p>4000°K</p> <p>940M1: 28 W/m 2500 lm/m</p> <p>940M2: 40 W/m 3400 lm/m</p> <p>940M3: 56 W/m 4450 lm/m</p>	<p>C Built-in driver, non-dimmable</p> <p>D Built-in driver, DALI</p> <p>E Built-in driver, 1-10V</p>	65 IP65	<p>BS Black Smooth</p> <p>WS White Smooth</p> <p>GS Gray Smooth</p>	<p>30 30 cm</p> <p>60 60 cm</p> <p>90 90 cm</p>
<p>Wiring</p> <p>BB Back feeding, Beginning</p> <p>BI Back feeding, Individual</p> <p>HB Hidden feeding, Beginning</p> <p>HI Hidden feeding, Individual</p> <p>M Middle</p> <p>E End</p>				

We reserve the right to make technical changes without prior notice