

# LIGHTWAY 5 – OUTDOOR / SYMMETRICAL BAFFLES FLOOR FIXED BRACKET

The Lightway 5 outdoor symmetrical baffles is developed maximum performance in harsh environmental conditions. Made from extruded aluminum, this IP65 element benefits from a wide variety of outputs & mountings. The baffles offer excellent glare control and are compatible with a wide array of beam angles, generating a powerful overall lighting effect.

- Diverse options of beam angles: very narrow, narrow, medium, wide and elliptical
- Excellent glare control and visual cutoff. Transversal & longitudinal shielding angle (45°)
- Delivers High levels of light
- Integrates with any architecture.



## Luminaire

**Application:** Ambient  
**Body Material:** Extruded aluminium

## Installation


**Ambient Temperature:** -10 to 50°C

## Optics


**Optic Type:** UV stabilized TIR Lens  
**Glare Control Device:** Aluminium Anti-Glare Baffles

## Electrical equipment


**Mains Voltage:** 220-240 VAC 50/60 Hz  
**Control Gear Efficacy:** > 85%



## Polar Curve



Medium Beam, 30° /  
LOR: 64%



Wide Beam, 45° /  
LOR: 48.4%

We reserve the right to make technical changes without prior notice

# LIGHTWAY 5 – OUTDOOR / SYMMETRICAL BAFFLES

## FLOOR FIXED BRACKET

### Code Index:

<u>L</u> <u>5</u>	<u>O</u>	<u>F</u> <u>1</u>	<u>X</u>					<u>6</u> <u>6</u>			
Family	Environment	Mounting	Glare Control Accessory	Optic	Beam Angle	CRI/CCT & Power	Control	IP	Body Finish	Length	Wiring
				AB	30	927P1	C		BT	30	SI
				AG	45	927P2	D		WS	60	SB
				AW		927P3	E		GS	90	SM
						930P1				120	SE
						930P2					
						930P3					
						940P1					
						940P2					
						940P3					

<b>Family</b>	<b>Environment</b>	<b>Mounting</b>	<b>Glare Control Accessory</b>	<b>Optic</b>	<b>Beam Angle</b>
L5 Lightway 5	O Outdoor	F1 Floor Fixed Bracket	X N/A	AB Black Symmetrical Baffles AG Gray Symmetrical Baffles AW White Symmetrical Baffles	30 Medium Beam, 30° 45 Wide Beam, 45°
<b>CRI/CCT &amp; Power</b>		<b>Control</b>	<b>IP</b>	<b>Body Finish</b>	
	LED Load initial Lumen	C Built-in driver, non-dimmable D Built-in driver, DALI E Built-in driver, 1-10V	66 IP66	BT Black Textured WS White Smooth GS Gray Smooth	
2700°K	927P1: 20 W/m 1700 lm/m 927P2: 30 W/m 2250 lm/m 927P3: 42 W/m 3000 lm/m				
3000°K	930P1: 20 W/m 1700 lm/m 930P2: 30 W/m 2400 lm/m 930P3: 42 W/m 3100 lm/m				
4000°K	940P1: 20 W/m 1900 lm/m 940P2: 30 W/m 2550 lm/m 940P3: 42 W/m 3300 lm/m				

<b>Length</b>	<b>Wiring</b>
30 30 cm	SI Side feeding, Individual
60 60 cm	SB Side feeding, Beginning
90 90 cm	SM Side feeding, Middle
120 120 cm	SE Side feeding, End

We reserve the right to make technical changes without prior notice