

# LIGHTWAY 5 – OUTDOOR / GRAZER BEAM

## ADJUSTABLE BRACKET

The Lightway 5 Outdoor beam is developed for maximum performance in harsh environmental conditions. Made from extruded aluminum, this IP65 element benefits from a wide variety of outputs. The Beam compatible with a wide array of beam angles, generating a powerful overall lighting effect.

The fixture is available with an aluminum anti glare shield that gives control over the light for increased visual comfort.

- Diverse options of beam angles: very narrow, narrow, medium, wide and elliptic
- Delivers High levels of light
- Integrates with any architecture.



### Luminaire

Application: Grazer  
Body Material: Extruded aluminium

### Installation

Ambient Temperature: -10 to 50°C


### Optics

Optic Type: UV stabilized TIR Lens


### Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz  
Control Gear Efficacy: > 85%


### Polar Curve






Narrow Beam, 8° /  
LOR: 79.2%



Narrow Beam, 15° /  
LOR: 67.4%





Narrow Beam, 8° /  
LOR: 79.2%



Tous droits réservés. Toute réimpression ou utilisation non autorisée sans la permission écrite de la VICE Lighting est formellement interdite.



# LIGHTWAY 5 – OUTDOOR / GRAZER BEAM ADJUSTABLE BRACKET



*We reserve the right to make technical changes without prior notice*

# LIGHTWAY 5 – OUTDOOR / GRAZER BEAM ADJUSTABLE BRACKET

## Code Index:

<u>L</u> <u>5</u>	<u>O</u>	<u>S</u> <u>1</u>	<u>—</u>	<u>G</u> <u>I</u>	<u>—</u>	<u>—</u>	<u>—</u>	<u>—</u>	<u>6</u> <u>6</u>	<u>—</u>	<u>—</u>	<u>—</u>
Family	Environment	Mounting	Glare Control Accessory	Optic	Beam Angle	CRI/CCT & Power	Control	IP	Body Finish	Length	Wiring	
			X		08	927P1	C		BT	30	BI	
			S		15	927P2	D		WS	60	BB	
						927P3	E		GS	90	BM	
						930P1				120	BE	
						930P2					SI	
						930P3					SB	
						940P1					SM	
						940P2					SE	
						940P3						

Family	Environment	Mounting	Glare Control Accessory	Optic	Beam Angle
L5 Lightway 5	O Outdoor	S1 Adjustable Bracket	X N/A S With Anti-Glare Shield	GT Beam	08 Narrow Beam, 8° 15 Narrow Beam, 15°

CRI/CCT & Power	Control	IP	Body Finish
LED Load initial Lumen 2700°K <b>927P1:</b> 20 W/m 1700 lm/m <b>927P2:</b> 30 W/m 2250 lm/m <b>927P3:</b> 42 W/m 3000 lm/m <hr/> 3000°K <b>930P1:</b> 20 W/m 1700 lm/m <b>930P2:</b> 30 W/m 2400 lm/m <b>930P3:</b> 42 W/m 3100 lm/m <hr/> 4000°K <b>940P1:</b> 20 W/m 1900 lm/m <b>940P2:</b> 30 W/m 2550 lm/m <b>940P3:</b> 42 W/m 3300 lm/m	<b>C</b> Built-in driver, non-dimmable <b>D</b> Built-in driver, DALI <b>E</b> Built-in driver, 1-10V	66 IP66	<b>BT</b> Black Textured <b>WS</b> White Smooth <b>GS</b> Gray Smooth

Length	Wiring
30 30 cm	<b>BI</b> Bottom feeding, Individual
60 60 cm	<b>BB</b> Bottom feeding, Beginning
90 90 cm	<b>BM</b> Bottom feeding, Middle
120 120 cm	<b>BE</b> Bottom feeding, End
	<b>SI</b> Side feeding, Individual
	<b>SB</b> Side feeding, Beginning
	<b>SM</b> Side feeding, Middle
	<b>SE</b> Side feeding, End

We reserve the right to make technical changes without prior notice