

LIGHTWAY 5 – OUTDOOR / WASHER BEAM

ADJUSTABLE BRACKET

The Lightway 5 Outdoor beam is developed for maximum performance in harsh environmental conditions. Made from extruded aluminum, this IP65 element benefits from a wide variety of outputs. The Beam compatible with a wide array of beam angles, generating a powerful overall lighting effect.

The fixture is available with an aluminum anti glare shield that gives control over the light for increased visual comfort.

- Diverse options of beam angles: very narrow, narrow, medium, wide and elliptic
- Delivers High levels of light
- Integrates with any architecture.



Luminaire

Application: Washer
Body Material: Extruded aluminium

Installation

Operating Temperature: -10 to 50°C


Optics

Optic Type: UV stabilized TIR Lens


Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%


Polar Curve




Asymmetrical / LOR: 68.9






Elliptical beam 10° x 54° / LOR: 58.1%



Elliptical beam 10° x 54° / LOR: 62.6%




Elliptical beam 15° x 36° / LOR: 58.1%



We reserve the right to make technical changes without prior notice



LIGHTWAY 5 – OUTDOOR / WASHER BEAM ADJUSTABLE BRACKET



We reserve the right to make technical changes without prior notice

LIGHTWAY 5 – OUTDOOR / WASHER BEAM ADJUSTABLE BRACKET

Code Index:

<u>L 5</u>	<u>O</u>	<u>S 1</u>		<u>W T</u>				<u>6 6</u>					
Family	Environment	Mounting	Glare Control	Accessory	Optic	Beam Angle	CRI/CCT & Power	Control	IP	Body Finish	Length	Feeding	Wiring
			X			W1	927P1	C		B	30	B	I
			S			E1	927P2	D		W	60	S	B
						E2	927P3	E		G	90		M
							930P1				120		E
							930P2						S
							930P3						
							940P1						
							940P2						
							940P3						
							9TW						

Family L5 Lightway 5	Environment O Outdoor	Mounting S1 Adjustable Bracket	Glare Control Accessory X N/A S With Anti-Glare Shield	Optic WT Beam	Beam Angle W1 Asymmetrical E1 Elliptical beam 10° x 54° E2 Elliptical beam 15° x 36°																																							
CRI/CCT & Power	Control	IP	Body Finish																																									
<table border="1"> <thead> <tr> <th></th> <th>LED Load</th> <th>initial Lumen</th> </tr> </thead> <tbody> <tr> <td>2700°K</td> <td>927P1: 20 W/m</td> <td>1700 lm/m</td> </tr> <tr> <td></td> <td>927P2: 30 W/m</td> <td>2250 lm/m</td> </tr> <tr> <td></td> <td>927P3: 42 W/m</td> <td>3000 lm/m</td> </tr> <tr> <td>3000°K</td> <td>930P1: 20 W/m</td> <td>1700 lm/m</td> </tr> <tr> <td></td> <td>930P2: 30 W/m</td> <td>2400 lm/m</td> </tr> <tr> <td></td> <td>930P3: 42 W/m</td> <td>3100 lm/m</td> </tr> <tr> <td>4000°K</td> <td>940P1: 20 W/m</td> <td>1900 lm/m</td> </tr> <tr> <td></td> <td>940P2: 30 W/m</td> <td>2550 lm/m</td> </tr> <tr> <td></td> <td>940P3: 42 W/m</td> <td>3300 lm/m</td> </tr> <tr> <td>Tunable White</td> <td>9TWP1: 20 W/m</td> <td>2560 lm/m</td> </tr> <tr> <td></td> <td>9TWP2: 30 W/m</td> <td>3650 lm/m</td> </tr> <tr> <td></td> <td>9TWP3: 42 W/m</td> <td>4730 lm/m</td> </tr> </tbody> </table>		LED Load	initial Lumen	2700°K	927P1: 20 W/m	1700 lm/m		927P2: 30 W/m	2250 lm/m		927P3: 42 W/m	3000 lm/m	3000°K	930P1: 20 W/m	1700 lm/m		930P2: 30 W/m	2400 lm/m		930P3: 42 W/m	3100 lm/m	4000°K	940P1: 20 W/m	1900 lm/m		940P2: 30 W/m	2550 lm/m		940P3: 42 W/m	3300 lm/m	Tunable White	9TWP1: 20 W/m	2560 lm/m		9TWP2: 30 W/m	3650 lm/m		9TWP3: 42 W/m	4730 lm/m	C Non-dimmable D DALI Dimmable D DALI Type 8 E 1-10V Dimmable	66 IP66	B Black W White G Gray		
	LED Load	initial Lumen																																										
2700°K	927P1: 20 W/m	1700 lm/m																																										
	927P2: 30 W/m	2250 lm/m																																										
	927P3: 42 W/m	3000 lm/m																																										
3000°K	930P1: 20 W/m	1700 lm/m																																										
	930P2: 30 W/m	2400 lm/m																																										
	930P3: 42 W/m	3100 lm/m																																										
4000°K	940P1: 20 W/m	1900 lm/m																																										
	940P2: 30 W/m	2550 lm/m																																										
	940P3: 42 W/m	3300 lm/m																																										
Tunable White	9TWP1: 20 W/m	2560 lm/m																																										
	9TWP2: 30 W/m	3650 lm/m																																										
	9TWP3: 42 W/m	4730 lm/m																																										

Length 30 30 cm 60 60 cm 90 90 cm 120 120 cm	Feeding B Bottom S Side	Wiring I Individual B Beginning M Middle E End S Side
---	--------------------------------------	---

We reserve the right to make technical changes without prior notice