

ZINC UNO / GRAZER

SURFACE MOUNTED

Zinc is designed to contrast with the existing blocky floodlights and spotlights. The Uno showcases a compact high-performance tool that can host a multitude of optics which allows this product to be used in all kinds of Architectural and urban applications.

Zinc line leaves minimal physical impact while blending smoothly within its environment. In spite the compact design Zinc luminaires can host different optics to serve different lighting situations.

This product can be mounted vertically or horizontally and has a tilt adjustment up to 90°, allowing designers to illuminate horizontal, sloped, and vertical surfaces alike.

This system is available with fine mesh shield that secure glare control and conducive visual comfort.

Product Features:

- Homogeneous color mixing within one reflector
- IP 65
- Different optics serving different lighting application:
 - o Wall washer
 - o Wall grazer
 - o Flood light

IP65

Ik06



Luminaire

Application: Grazer
Body Material: Extruded aluminium

Installation



Ambient Temperature: -10 to 40°C

Optics

Optic Type: UV stabilized TIR Lens
Surface Diffuser: No Diffuser

Electrical equipment


Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%



We reserve the right to make technical changes without prior notice

ZINC / GRAZER SURFACE MOUNTED

Mounting Ratio



100 to 150 mm

Setback from the wall is defined by wall texture and height. Consult factory for optimal setback according to your project conditions.

ZINC / GRAZER SURFACE MOUNTED

Code Index:

<u>Z 3</u>	<u>U</u>	<u>O S M</u>	<u>---</u>	<u>G I</u>	<u>1 3</u>	<u>-----</u>	<u>---</u>	<u>6 5</u>	<u>---</u>	<u>O 8</u>	<u>---</u>	
Family	Product	Mounting	Glare Control	Accessory	Optic	Beam Angle	CRI/CCT & Power	Control	IP	Body Finish	Length	Wiring
			L				927C1	C		BS		BI
			X				927C2	K		WS		HI
							930C1	L		GS		
							930C2					
							940C1					
							940C2					

Family	Product	Mounting	Glare Control Accessory	Optic	Beam Angle
Z3 Zinc	U Uno	OSM Surface Mounted	L With Anti-Glare Louvre X Without Anti-Glare Louvre	GT Beam	13 Narrow Beam, 13°

CRI/CCT & Power	Control	IP	Body Finish												
<table border="1"> <thead> <tr> <th></th> <th>LED Load</th> <th>initial Lumen</th> </tr> </thead> <tbody> <tr> <td>2700°K</td> <td>927C1: 4.2 W 927C2: 6 W</td> <td>330 lm 430 lm</td> </tr> <tr> <td>3000°K</td> <td>930C1: 4.2 W 930C2: 6 W</td> <td>350 lm 460 lm</td> </tr> <tr> <td>4000°K</td> <td>940C1: 4.2 W 940C2: 6 W</td> <td>380 lm 490 lm</td> </tr> </tbody> </table>		LED Load	initial Lumen	2700°K	927C1: 4.2 W 927C2: 6 W	330 lm 430 lm	3000°K	930C1: 4.2 W 930C2: 6 W	350 lm 460 lm	4000°K	940C1: 4.2 W 940C2: 6 W	380 lm 490 lm	C Built-in driver, non-dimmable K Remote driver, DALI L Remote driver, 1-10V	65 IP65	BS Black Smooth WS White Smooth GS Gray Smooth
	LED Load	initial Lumen													
2700°K	927C1: 4.2 W 927C2: 6 W	330 lm 430 lm													
3000°K	930C1: 4.2 W 930C2: 6 W	350 lm 460 lm													
4000°K	940C1: 4.2 W 940C2: 6 W	380 lm 490 lm													

Length	Wiring
O8 8 cm	BI Back feeding HI Hidden feeding

We reserve the right to make technical changes without prior notice