

# STARDROP / DARKWAY

## SURFACE MOUNTED

The stardrop is quite adaptable to well integrate into the space ratio and requirements. The stardrop device can be either ceiling mounted or pendant. The number of spots can be modified in every unit. This product offers high visual comfort, ideal for residential and commercial spaces.

- Clean square light distribution from 25mm round aperture reflectors. The optimal beam angle over field angle ratio offers a highly-uniform horizontal surface
- Flexibility of mounting height with 3 beam angles
- Homogeneous color mixing within one reflector



### Luminaire


**Application:** Ambient  
**Body Material:** Extruded aluminium

### Optics


**Optic Type:** Special reflector of complex microfaceted surface  
**Glare Control Device:** Cinco Cell Baffles  
**Surface Diffuser:** No Diffuser

### Electrical equipment


**Mains Voltage:** 220-240 VAC 50/60 Hz  
**Control Gear Efficacy:** > 85%



### Polar Curve



Narrow Beam, 36° /  
LOR: 70.3%




Medium Beam, 50° /  
LOR: 90.4%

We reserve the right to make technical changes without prior notice

# STARDROP / DARKWAY

## SURFACE MOUNTED



Wide Beam, 60° /  
LOR: 88.5%

*We reserve the right to make technical changes without prior notice*

# STARDROP / DARKWAY

## SURFACE MOUNTED

### Code Index:

| <u>S</u> | <u>D</u>    | <u>I</u> | <u>S</u> | <u>M</u>      | <u>R</u> | <u>1</u>   | <u>D</u>        | --      | ---- | --          | <u>2</u> | <u>0</u> | -- | <u>I</u> | <u>2</u> | <u>0</u> |
|----------|-------------|----------|----------|---------------|----------|------------|-----------------|---------|------|-------------|----------|----------|----|----------|----------|----------|
| Family   | Environment | Mounting | Shape    | Number of LED | Optic    | Beam Angle | CRI/CCT & Power | Control | IP   | Body Finish | Layout   | Length   |    |          |          |          |
|          |             |          |          |               |          | SN         | 927E1           | J       |      | BS          |          |          |    |          |          |          |
|          |             |          |          |               |          | SM         | 927E2           | K       |      | BT          |          |          |    |          |          |          |
|          |             |          |          |               |          | SW         | 927E3           | L       |      | WS          |          |          |    |          |          |          |
|          |             |          |          |               |          |            | 930E1           |         |      | WT          |          |          |    |          |          |          |
|          |             |          |          |               |          |            | 930E2           |         |      | GS          |          |          |    |          |          |          |
|          |             |          |          |               |          |            | 930E3           |         |      |             |          |          |    |          |          |          |
|          |             |          |          |               |          |            | 940E1           |         |      |             |          |          |    |          |          |          |
|          |             |          |          |               |          |            | 940E2           |         |      |             |          |          |    |          |          |          |
|          |             |          |          |               |          |            | 940E3           |         |      |             |          |          |    |          |          |          |

**Family**  
SD Stardrop

**Environment**  
I Indoor

**Mounting**  
SM Surface Mounted

**Shape**  
R Round

**Number of LED**  
11 LED

**Optic**  
D Darkway

**Beam Angle**  
SN Narrow Beam, 36°  
SM Medium Beam, 50°  
SW Wide Beam, 60°

**CRI/CCT & Power**

|               | LED Load                | initial Lumen |
|---------------|-------------------------|---------------|
| <b>2700°K</b> | <b>927E1:</b> 0.3 W/ft  | 100 lm        |
|               | <b>927E2:</b> 0.45 W/ft | 140 lm        |
|               | <b>927E3:</b> 0.6 W/ft  | 180 lm        |
| <b>3000°K</b> | <b>930E1:</b> 0.3 W/ft  | 110 lm        |
|               | <b>930E2:</b> 0.45 W/ft | 150 lm        |
|               | <b>930E3:</b> 0.6 W/ft  | 190 lm        |
| <b>4000°K</b> | <b>940E1:</b> 0.3 W/ft  | 110 lm        |
|               | <b>940E2:</b> 0.45 W/ft | 150 lm        |
|               | <b>940E3:</b> 0.6 W/ft  | 200 lm        |

**Control**  
J Remote driver, non-dimmable  
K Remote driver, DALI  
L Remote driver, 1-10V

**IP**  
20 IP20

**Body Finish**  
BS Black Smooth  
BT Black Fine Textured  
WS White Smooth  
WT White Textured  
GS Gray Smooth

**Layout**  
I I Shape

**Length**  
20 20 cm

We reserve the right to make technical changes without prior notice