

ZINC UNO / FLOODLIGHT SURFACE MOUNTED

Zinc is designed to contrast with the existing blocky floodlights and spotlights. The Uno showcases a compact high-performance tool that can host a multitude of optics which allows this product to be used in all kinds of Architectural and urban applications.

Zinc line leaves minimal physical impact while blending smoothly within its environment. In spite the compact design Zinc luminaires can host different optics to serve different lighting situations.

This product can be mounted vertically or horizontally and has a tilt adjustment up to 90°, allowing designers to illuminate horizontal, sloped, and vertical surfaces alike.

Product Features:

- Homogeneous color mixing within one reflector
- IP 66
- Different optics serving different lighting application:
 - o Wall washer
 - o Wall grazer
 - o Flood light



Luminaire


Product Type: Ambient
Body Material: Extruded aluminium

Optics


Optic Type: UV stabilized TIR Lens
Surface diffuser: No Diffuser

Electrical equipment


Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%




Polar Curves



Medium Beam, 30° /
LOR: 82%




Wide Beam, 45° /
LOR: 65.4%



Elliptical beam 10° x 54° /
LOR: 72%

We reserve the right to make technical changes without prior notice

ZINC / FLOODLIGHT SURFACE MOUNTED



Elliptical beam 15° x 36° /
LOR: 78%

ZINC / FLOODLIGHT

SURFACE MOUNTED

Code Index:

<u>Z 3</u>	<u>U</u>	<u>O S M</u>	<u>A T</u>	<u>---</u>	<u>-----</u>	<u>-</u>	<u>6 6</u>	<u>---</u>	<u>N</u>	<u>I</u>	<u>O 8</u>
Family	Product	Mounting	Application	Beam Angle	CRI/CCT & Power	Dimming	IP	Body finish	Emergency	Layout	Length
				30	92701	C		BS			
				45	92702	J		WS			
				E1	92703	K		GS			
				E2	93001	L					
					93002	M					
					93003						
					94001						
					94002						
					94003						

Family	Product	Mounting	Application	Beam Angle	CRI/CCT & Power	Dimming	IP	Body finish	Emergency
Z3 Zinc	U Uno	OSM Surface Mounted	AT Floodlight, Beam	30 Medium Beam, 30° 45 Wide Beam, 45° E1 Elliptical beam 10° x 54° E2 Elliptical beam 15° x 36°	LED Load initial Lumen 2700°K 92701: 1 W 100 lm 92702: 1.5 W 135 lm 92703: 2 W 175 lm 3000°K 93001: 1 W 110 lm 93002: 1.5 W 150 lm 93003: 2 W 200 lm 4000°K 94001: 1 W 115 lm 94002: 1.5 W 155 lm 94003: 2 W 210 lm	C Built-in driver, non dimmable J Remote driver, non dimmable K Remote driver, DALI L Remote driver, 1-10V M Remote driver, Phase dim	66 IP66	BS Black Smooth WS White Smooth GS Gray Smooth	N No Emergency

Layout	Length
I I Shape	O8 8 cm

We reserve the right to make technical changes without prior notice