

LIGHTWAY 5 – OUTDOOR / GRAZING BAFFLES

FLOOR FIXED BRACKET

The Lightway 5 outdoor grazing baffles is developed for maximum performance in harsh environmental conditions. Made from extruded aluminum, this IP65 element benefits from specially-designed aluminum optics totally glare free from both the longitudinal and transversal sides of the profile, achieving a powerful effect while emphasizing rough-textured surfaces of great height.

- Best-in-class vertical surface grazing, Scallop-free lighting from zero start point of vertical surfaces
- Glare-free in both longitudinal and transversal sides
- 5 to 10cm from edge of fixture to surface of the wall depending on its height and surface.
- Use of continuous fixtures to within 10cm of side walls – Integrates with any architecture.



Luminaire

Application: Grazer
Body Material: Extruded aluminium

Installation

Operating Temperature: -10 to 50°C


Optics

Optic Type: UV stabilized TIR Lens
Glare Control Device: Aluminium Anti-Glare Baffles


Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%


Polar Curve



Narrow Beam, 8° /
LOR: 35.5%



Narrow Beam, 15°
/ LOR: 30.0%



LIGHTWAY 5 – OUTDOOR / GRAZING BAFFLES

FLOOR FIXED BRACKET

Code Index:

<u>L 5</u>	<u>O</u>	<u>F 1</u>	<u>X</u>	---	---	-----	---	<u>6 5</u>	---	---	<u>S</u>	---	
Family	Environment	Mounting	Glare Control	Accessory	Optic	Beam Angle	CRI/CCT & Power	Control	IP	Body Finish	Length	Feeding	Wiring
					GB	08	927P1	C		BT	30		I
					GG	15	927P2	D		WS	60		B
					GW		927P3	E		GS	90		M
							930P1				120		E
							930P2						
							930P3						
							940P1						
							940P2						
							940P3						

Family L5 Lightway 5	Environment O Outdoor	Mounting F1 Floor Fixed Bracket	Glare Control Accessory X N/A	Optic GB Black Grazing Baffles GG Gray Grazing Baffles GW White Grazing Baffles	Beam Angle 08 Narrow Beam, 8° 15 Narrow Beam, 15°
--------------------------------	---------------------------------	---	---	---	--

CRI/CCT & Power	Control	IP	Body Finish																														
<table border="0"> <tr> <td></td> <td>LED Load</td> <td>initial Lumen</td> </tr> <tr> <td>2700°K</td> <td>927P1: 20 W/m</td> <td>1700 lm/m</td> </tr> <tr> <td></td> <td>927P2: 30 W/m</td> <td>2250 lm/m</td> </tr> <tr> <td></td> <td>927P3: 42 W/m</td> <td>3000 lm/m</td> </tr> <tr> <td>3000°K</td> <td>930P1: 20 W/m</td> <td>1700 lm/m</td> </tr> <tr> <td></td> <td>930P2: 30 W/m</td> <td>2400 lm/m</td> </tr> <tr> <td></td> <td>930P3: 42 W/m</td> <td>3100 lm/m</td> </tr> <tr> <td>4000°K</td> <td>940P1: 20 W/m</td> <td>1900 lm/m</td> </tr> <tr> <td></td> <td>940P2: 30 W/m</td> <td>2550 lm/m</td> </tr> <tr> <td></td> <td>940P3: 42 W/m</td> <td>3300 lm/m</td> </tr> </table>		LED Load	initial Lumen	2700°K	927P1: 20 W/m	1700 lm/m		927P2: 30 W/m	2250 lm/m		927P3: 42 W/m	3000 lm/m	3000°K	930P1: 20 W/m	1700 lm/m		930P2: 30 W/m	2400 lm/m		930P3: 42 W/m	3100 lm/m	4000°K	940P1: 20 W/m	1900 lm/m		940P2: 30 W/m	2550 lm/m		940P3: 42 W/m	3300 lm/m	C Non-dimmable D DALI Dimmable E 1-10V Dimmable	65 IP65	BT Black WS White GS Gray
	LED Load	initial Lumen																															
2700°K	927P1: 20 W/m	1700 lm/m																															
	927P2: 30 W/m	2250 lm/m																															
	927P3: 42 W/m	3000 lm/m																															
3000°K	930P1: 20 W/m	1700 lm/m																															
	930P2: 30 W/m	2400 lm/m																															
	930P3: 42 W/m	3100 lm/m																															
4000°K	940P1: 20 W/m	1900 lm/m																															
	940P2: 30 W/m	2550 lm/m																															
	940P3: 42 W/m	3300 lm/m																															

Length	Feeding	Wiring
30 30 cm 60 60 cm 90 90 cm 120 120 cm	S Side	I Individual B Beginning M Middle E End

We reserve the right to make technical changes without prior notice