

LIGHTWAY 5 – OUTDOOR / GRAZER BEAM

ADJUSTABLE BRACKET

The Lightway 5 Outdoor beam is developed for maximum performance in harsh environmental conditions. Made from extruded aluminum, this IP65 element benefits from a wide variety of outputs. The Beam compatible with a wide array of beam angles, generating a powerful overall lighting effect.

The fixture is available with an aluminum anti glare shield that gives control over the light for increased visual comfort.

- Diverse options of beam angles: very narrow, narrow, medium, wide and elliptic
- Delivers High levels of light
- Integrates with any architecture.



Luminaire

Application: Grazer
 Body Material: Extruded aluminium

Installation

Ambient Temperature: -10 to 50°C


Optics

Optic Type: UV stabilized TIR Lens


Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz
 Control Gear Efficacy: > 85%


Polar Curve






Narrow Beam, 8° /
LOR: 79.2%



Narrow Beam, 15° /
LOR: 67.4%





Narrow Beam, 8° /
LOR: 79.2%



Tous droits réservés. Toute réimpression ou utilisation non autorisée sans la permission écrite de la VICE Lighting est formellement interdite.



LIGHTWAY 5 – OUTDOOR / GRAZER BEAM ADJUSTABLE BRACKET



We reserve the right to make technical changes without prior notice

LIGHTWAY 5 – OUTDOOR / GRAZER BEAM ADJUSTABLE BRACKET

Code Index:

<u>L</u> <u>5</u>	<u>O</u>	<u>S</u> <u>1</u>	<u>—</u>	<u>G</u> <u>I</u>	<u>—</u>	<u>—</u>	<u>—</u>	<u>—</u>	<u>6</u> <u>6</u>	<u>—</u>	<u>—</u>	<u>—</u>
Family	Environment	Mounting	Glare Control Accessory	Optic	Beam Angle	CRI/CCT & Power	Control	IP	Body Finish	Length	Wiring	
			X		08	927P1	C		BT	30	BI	
			S		15	927P2	D		WS	60	BB	
						927P3	E		GS	90	BM	
						930P1				120	BE	
						930P2					SI	
						930P3					SB	
						940P1					SM	
						940P2					SE	
						940P3						

Family	Environment	Mounting	Glare Control Accessory	Optic	Beam Angle
L5 Lightway 5	O Outdoor	S1 Adjustable Bracket	X N/A S With Anti-Glare Shield	GT Beam	08 Narrow Beam, 8° 15 Narrow Beam, 15°

CRI/CCT & Power	Control	IP	Body Finish
<p>LED Load initial Lumen</p> <p>2700°K 927P1: 20 W/m 1700 lm/m 927P2: 30 W/m 2250 lm/m 927P3: 42 W/m 3000 lm/m</p> <p>3000°K 930P1: 20 W/m 1700 lm/m 930P2: 30 W/m 2400 lm/m 930P3: 42 W/m 3100 lm/m</p> <p>4000°K 940P1: 20 W/m 1900 lm/m 940P2: 30 W/m 2550 lm/m 940P3: 42 W/m 3300 lm/m</p>	<p>C Built-in driver, non-dimmable</p> <p>D Built-in driver, DALI</p> <p>E Built-in driver, 1-10V</p>	66 IP66	<p>BT Black Textured</p> <p>WS White Smooth</p> <p>GS Gray Smooth</p>

Length	Wiring
30 30 cm	BI Bottom feeding, Individual
60 60 cm	BB Bottom feeding, Beginning
90 90 cm	BM Bottom feeding, Middle
120 120 cm	BE Bottom feeding, End
	SI Side feeding, Individual
	SB Side feeding, Beginning
	SM Side feeding, Middle
	SE Side feeding, End

We reserve the right to make technical changes without prior notice